

XPan HASSELBLAD 5.6/30

CLOSE FOCUS RANGE DATA:

Minimum distance object to film

Corresponding distance object to front lens

Maximum image scale

Corresponding area of coverage

Corresponding exposure reduction

0.70 m

0.62 m

1: 20


48 x 130 cm

0.1 f-stop

ENTRANCE PUPIL POSITION

63 mm in front of the film plane. (at infinite focus setting):


The entrance pupil position is the correct position of the axis of rotation when making a panorama image by combining individual images of a scene.




MTF

Modulation Transfer as a function of image height at infinite focus setting.

Sagittal slit orientation drawn with continuous line and tangential with dashed. White light. Spatial frequencies 10, 20 and 40 lp/mm





XPan HASSELBLAD 5.6/30

DEPTH-OF-FIELD DATA

Given distances are calculated for a blur circle diameter of 33 microns and do not include the effect of lens aberrations.

Depth-of-field in meters			
	f/5.6	f/11	f/22
∞	5 - ∞	2.5 - ∞	1.3 - ∞
10 m	3.5 - ∞	2 - ∞	1.2 - ∞
5 m	2.5 - ∞	1.8 - ∞	1.1 - ∞
3 m	1.9 - 7	1.5 - ∞	1 - ∞
2 m	1.5 - 3.2	1.2 - 8	0.85 - ∞
1.5 m	1.2 - 2.1	1 - 3.3	0.75 - ∞
1.2 m	1 - 1.5	0.85 - 2.1	0.7 - 9
1 m	0.85 - 1.2	0.75 - 1.5	0.6 - 3.5
0.8 m	0.71 - 0.92	0.65 - 1.1	0.55 - 1.7

To convert meters into feet, multiply by 3.281. To convert meters into inches, multiply by 39.37